

Please type a plus sign (+) inside this box → ☒

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.	KWI-003
First Inventor	KWITEK, Benjamin J.
Title	Viscoelastic Grip for a Writing...
Express Mail Label No.	

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1. ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
2. ☒ Applicant claims small entity status.
See 37 CFR 1.27.
3. ☒ Specification [Total Pages **25**]
(preferred arrangement set forth below)
- Descriptive title of the invention
 - Cross Reference to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to sequence listing, a table, or a computer program listing appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
4. ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets **9**]
5. Oath or Declaration [Total Pages **5**]
- a. ☒ Newly executed (original or copy)
Copy from a prior application (37 CFR 1.63 (d))
(for continuation/divisional with Box 17 completed)
- b. ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s)
named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
6. ☐ Application Data Sheet. See 37 CFR 1.76

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

7. ☐ CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix)
8. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
- a. ☐ Computer Readable Form (CRF)
- b. Specification Sequence Listing on:
- i. ☐ CD-ROM or CD-R (2 copies); or
- ii. ☐ paper
- c. ☐ Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

9. ☐ Assignment Papers (cover sheet & document(s))
10. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
11. ☐ English Translation Document (if applicable)
12. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
13. ☐ Preliminary Amendment
14. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76:

☐ Continuation ☐ Divisional ☒ Continuation-in-part (CIP)
of prior application No.: **60** / **163,259**

Prior application information: Examiner

Group / Art Unit:

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

18. CORRESPONDENCE ADDRESS☒ Customer Number or Bar Code Label**021884**

(Insert Customer No. or Attach bar code label here)

or ☐ Correspondence address below

Name

Address

City

State

Zip Code

Country

Telephone

Fax

Name (Print/Type)

Howard N. Flaxman

Registration No. (Attorney/Agent)

34,595

Signature

Date **11/3/2000**

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

 JC825 U.S. PTO
09/704556

11/03/00

 did not receive the following
Post Card

FEE TRANSMITTAL for FY 2001

Patent fees are subject to annual revision.

TOTAL AMOUNT OF PAYMENT (\$) 355.00

Complete if Known

Application Number
Filing Date
First Named Inventor **KWITEK, Benjamin J.**
Examiner Name
Group Art Unit
Attorney Docket No. **KWI-003**

METHOD OF PAYMENT

1. ☒ The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to.

Deposit Account Number **01-2221**
Deposit Account Name **Aquilino & Welsh**

☒ Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17

☒ Applicant claims small entity status. See 37 CFR 1.27

2. ☒ Payment Enclosed:

☒ Check ☐ Credit card ☐ Money Order ☐ Other

FEE CALCULATION

1. BASIC FILING FEE

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
101 710	201 355	Utility filing fee	355
106 320	206 160	Design filing fee	
107 490	207 245	Plant filing fee	
108 710	208 355	Reissue filing fee	
114 150	214 75	Provisional filing fee	

SUBTOTAL (1) (\$) 355

2. EXTRA CLAIM FEES

Total Claims **20** -20** = X =
Independent Claims **2** -3** = X =
Multiple Dependent =

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description
103 18	203 9	Claims in excess of 20
102 80	202 40	Independent claims in excess of 3
104 270	204 135	Multiple dependent claim, if not paid
109 80	209 40	** Reissue independent claims over original patent
110 18	210 9	** Reissue claims in excess of 20 and over original patent

SUBTOTAL (2) (\$) 0

**or number previously paid, if greater; For Reissues, see above

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity Fee Code (\$)	Small Entity Fee Code (\$)	Fee Description	Fee Paid
105 130	205 65	Surcharge - late filing fee or oath	
127 50	227 25	Surcharge - late provisional filing fee or cover sheet	
139 130	139 130	Non-English specification	
147 2,520	147 2,520	For filing a request for <i>ex parte</i> reexamination	
112 920*	112 920*	Requesting publication of SIR prior to Examiner action	
113 1,840*	113 1,840*	Requesting publication of SIR after Examiner action	
115 110	215 55	Extension for reply within first month	
116 390	216 195	Extension for reply within second month	
117 890	217 445	Extension for reply within third month	
118 1,390	218 695	Extension for reply within fourth month	
128 1,890	228 945	Extension for reply within fifth month	
119 310	219 155	Notice of Appeal	
120 310	220 155	Filing a brief in support of an appeal	
121 270	221 135	Request for oral hearing	
138 1,510	138 1,510	Petition to institute a public use proceeding	
140 110	240 55	Petition to revive - unavoidable	
141 1,240	241 620	Petition to revive - unintentional	
142 1,240	242 620	Utility issue fee (or reissue)	
143 440	243 220	Design issue fee	
144 600	244 300	Plant issue fee	
122 130	122 130	Petitions to the Commissioner	
123 50	123 50	Petitions related to provisional applications	
126 240	126 240	Submission of Information Disclosure Stmt	
581 40	581 40	Recording each patent assignment per property (times number of properties)	
146 710	246 355	Filing a submission after final rejection (37 CFR § 1.129(a))	
149 710	249 355	For each additional invention to be examined (37 CFR § 1.129(b))	
179 710	279 355	Request for Continued Examination (RCE)	
169 900	169 900	Request for expedited examination of a design application	

Other fee (specify) _____

* Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$) 0

SUBMITTED BY

Name (Print/Type)	Registration No. (Attorney/Agent)	Telephone
Howard N. Flaxman	34,595	(703) 920-1122
Signature		Date 11/3/2000

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

KWI-003

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

INVENTOR: Benjamin J. Kwitek

TITLE: VISCOELASTIC GRIP FOR A WRITING IMPLEMENT

CROSS-REFERENCE TO RELATED APPLICATIONS

This U.S. Patent Application is based upon U.S. Provisional Patent Application Serial No. 60/163,259, filed November 3, 1999, and entitled "VISCOELASTIC GRIP FOR A WRITING IMPLEMENT". This U.S. patent application is further a Continuation-In-Part of U.S. Patent Application Serial No. 09/173,445, filed October 16, 1998, and entitled "GOLF GRIP", which is currently pending, and incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The invention relates to grips for hand held implements. More particularly, the invention relates to a writing implement grip including a responsive polymer designed to provide individuals with a soft and individually conforming hand and finger surface. While the present grip technology was developed with writing implements in mind, the present grip technology may be readily used with other hand held implements; for example, medical instruments, hand tools, utensils and sporting equipment.

2. Description of the Prior Art

The manner in which an individual grips a writing implement is critical to the comfort of the user as he or she moves the writing implement across a sheet of paper. With this in mind, the designers of writing implements have continually attempted to design writing

implements which enhance the comfort for those individuals using their implements.

Many of the techniques employed in prior art writing implements have made great strides in improving the comfort level associated with the continued use of writing implements. However, a need still exists for writing implements which enhance the comfort of individuals using the writing implements on a continual basis. The present invention provides a writing implement grip improving upon those grips disclosed in the prior art.

SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide a grip shaped and dimensioned for use with a writing implement. The grip includes a longitudinally extending tubular shell having an inner surface and an outer surface. The grip also includes a viscoelastic hand/finger surface formed about the outer surface of the tubular shell.

It is also an object of the present invention to provide a grip wherein the tubular shell includes a first end and a second end. The tubular shell further includes an outwardly extending first lip adjacent the first end of the tubular shell and a outwardly extending second lip adjacent the second end of the tubular shell, the first and second lips acting to retain the viscoelastic hand/finger surface in position on the tubular shell.

It is another object of the present invention to provide a grip wherein the first lip extends about the circumference of the tubular shell adjacent the first end of the tubular shell and the second lip extends about the circumference of the tubular shell adjacent the second end of the tubular shell.

It is a further object of the present invention to provide a grip wherein the viscoelastic hand/finger surface is a viscoelastic solid-phase polymer material.

It is also an object of the present invention to provide a grip wherein the viscoelastic solid-phase polymer material is a thermoplastic elastomer.

It is still another object of the present invention to provide a grip wherein the viscoelastic hand/finger surface is a viscous liquid material contained within an elastomeric

bag.

It is yet a further object of the present invention to provide a grip wherein the viscoelastic liquid material is a silicone gel or silicone oil.

5 It is also an object of the present invention to provide a grip wherein the grip is adapted for selective attachment to the writing implement.

It is another object of the present invention to provide a grip wherein the grip is integrally formed with the writing implement.

It is also an object of the present invention to provide a writing implement including a grip as described above.

10 Other objects and advantages of the present invention will become apparent from the following detailed description when viewed in conjunction with the accompanying drawings, which set forth certain embodiments of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a side view of a writing implement with the present grip mounted thereon.

Figure 2 is a cross-sectional view of a grip according to a preferred embodiment of the present invention.

5 Figure 3 is a cross-sectional view of a grip according to a further preferred embodiment of the present invention.

Figure 4 is a cross section of a writing implement with the present grip representing yet another embodiment of the present invention.

10 Figure 5 is a cross-sectional view of a grip according to a further preferred embodiment of the present invention.

Figure 6 is a cross-sectional view of the present golf grip.

Figure 7 is a perspective view of the present golf grip.

Figure 8 is a cross-sectional view of an alternate embodiment in accordance with the present invention.

15 Figure 9 is a perspective view of a further embodiment in accordance with the present invention.

Figure 10 is a top view of still another embodiment in accordance with the present invention.

20 Figure 11 is a perspective view of the embodiment disclosed in Figure 6 secured to a golf shaft.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The detailed embodiments of the present invention are disclosed herein. It should be understood, however, that the disclosed embodiments are merely exemplary of the invention, which may be embodied in various forms. Therefore, the details disclosed herein are not to be interpreted as limited, but merely as the basis for the claims and as a basis for teaching one skilled in the art how to make and/or use the invention.

With reference to Figures 1 through 5, a writing implement grip is disclosed. The grip is designed with a responsive and relatively viscoelastic hand/finger surface. The viscoelastic hand/finger surface provides individuals with a soft and individually conforming gripping surface. For example, and in accordance with a preferred embodiment of the present invention, the conformable, viscoelastic hand/finger surface is a responsive, solid-phase polymer material (Figures 1 and 2) or a gelatinous material interposed within a more resilient material to contain the gelatinous material (Figure 3).

The hand/finger surface of the present grip is an ultra-soft material. This endows the grip with an inherent tactile feel. The grip, as described herein, provides a tacky surface, essential and beneficial for gripping. As those skilled in the art will readily appreciate, the tack level may be readily adjusted with chemical and/or mechanical processing modification. The ultra-soft hand/finger surface can be measured in terms of hardness by the Shore A Durometer Test. The present grips have durometers in this scale between approximately 2 and 35, and more preferably 25 or less.

In accordance with a preferred embodiment of the present grip, and with reference to Figures 1 and 2, the grip 10 includes a shell 12 shaped and dimensioned to fit about the grip portion 14 of a convention writing implement 16. As such, the shell 12 includes an inner surface 18 shaped and dimensioned to fit about the main body 20 of the writing implement 16 at a position in line with the grip portion 14 thereof.

It is contemplated that the lower half, or grip portion 14, of the writing implement 16 may be formed with a recess or ridges shaped and dimensioned to engage the grip 10 as it is slipped onto the writing implement 16. In this way, the attached grip 10 will be substantially flush with the overall shape and dimensions of the main body 20 of the writing implement 16.

The outer surface 22 of the shell 12 is shaped and dimensioned to receive the viscoelastic hand/finger surface 24. The shell 12 includes a central section 26 about which the viscoelastic hand/finger surface 24 is positioned. The proximal end 28 and distal end 30 of the shell 12 are respectively provided with lips 32a, 32b circumferentially extending about the shell 12. The lips 32a, 32b are shaped and dimensioned to retain the viscoelastic hand/finger surface 24 about the central section 26 of the shell 12.

The shell 12 may maintain a constant diameter as it extends from the proximal end 28 to the distal end 30. The shape is determined based upon the writing implement for which the grip 10 is designed and may be readily varied without departing from the spirit of the present invention for adaptation to various writing implements. This allows the shell 12 to conform to the shape of conventional writing implements.

The shell 12 may be constructed from a variety of elastomers, such as, thermoplastics or thermosets including rubber or synthetic rubber-like materials. In accordance with a preferred embodiment of the present invention, the shell preferably has a Shore A hardness of 20-55. This firmness is necessary to maintain the shape of the grip. It also prevents damage from chemicals and oils, including those produced by human hands. However, other materials may be employed without departing from the spirit of the present invention.

In accordance with the embodiment disclosed in Figures 1 and 2, the viscoelastic hand/finger surface 24 is preferably a viscoelastic solid-phase polymer material. The viscoelastic solid-phase polymer material is preferably a styrenic thermoplastic elastomer containing, for example, KRATON, which is manufactured by Shell Chemical Company.

The viscoelastic hand/finger surface 24 is positioned about the shell 12, and between the proximal and distal lips 32a, 32b. The viscoelastic hand/finger surface 24 is preferably adhered to the central section 26 of the shell 12 by over-molding, co-molding or two-part molding. With related materials over-molding will create a chemical bond, in essence forging one piece containing assimilated parts. This produces a dual durometer grip. This grip would have the advantage of being soft and conformable while being durable and cost effective. It is also contemplated that the viscoelastic hand/finger surface 24 may be adhered to the central section 26 of the shell 12 with an adhesive. As those of ordinary skill in the art will certainly appreciate, other methods for securing the hand/finger surface 24 to the shell 12 may be employed without departing from the spirit of present invention. Where the viscoelastic

hand/finger surface 24 is formed from a responsive, and relatively viscoelastic solid-phase polymer material, the outer surface 22 of the viscoelastic hand/finger surface 24 is formed from the same viscoelastic material as the remainder of the hand/finger surface.

An alternate embodiment of the present invention is disclosed in Figure 3. The alternate embodiment is substantially similar to the embodiment described above with reference to Figures 1 and 2, but replaces the viscoelastic solid-phase polymer construction with a viscous liquid material contained in an elastomeric bag.

Specifically, the grip 110 includes a shell 112 shaped and dimensioned to fit about the grip portion 14 of a writing implement 16. As with the prior embodiment, the shell 112 includes a central section 126 about which the soft viscoelastic hand/finger surface 124 is positioned. The proximal and distal ends 128, 130 of the shell 112 are respectively provided with lips 130a, 130b. The lips 130a, 130b are shaped and dimensioned to retain the soft polymer material forming the hand/finger surface 124 about the central section 126 of the shell 112.

In accordance with the embodiment disclosed in Figure 3, the viscoelastic hand/finger surface 124 is a viscous liquid material 134 contained in an elastomeric bag 136. The viscous liquid 134 is preferably a silicone gel or oil and the elastomeric bag is preferably a silicone sheet or a thermoplastic elastomer. While preferred materials are disclosed above, other materials exhibiting similar properties may be used without departing from the spirit of the present invention.

The viscoelastic hand/finger surface 124 is preferably adhered to the central section 126 of the shell 112 with an adhesive. The attachment could also be accomplished by compressing both ends of the elastomeric bag 136 at the proximal and distal lips 130a, 130b with a chamber and gasket system. As those of ordinary skill in the art will certainly appreciate, other methods for securing the viscoelastic hand/finger surface to the shell may be employed without departing from the spirit of present invention.

The grips 10, 110 described above are designed for selective attachment to an existing writing implement in a manner allowing an individual to readily remove and replace the grips, if necessary. However, and as those skilled in the art will readily appreciate, the underlying concepts of the present grip may be applied in manufacturing an integrally formed writing implement/grip 200. Specifically, and with reference to Figure 4, the shell 212 of the grip 210 is integrally formed as part of the grip portion 214 of the writing implement 216 and the viscoelastic hand/finger surface 224 is coupled directly thereto. Other manufacturing techniques in accordance with the spirit of the present invention are certainly possible and considered to be well within the scope of the present invention.

In accordance with the preferred embodiments of the present invention, the soft polymer material forming the hand/finger surface is approximately 0.02 to 0.50 inches thick and the elastomeric shell is preferably less than 0.5 inches thick. In this way, the present grip substantially conforms to ergonomically desirable writing implement dimensions.

With reference to Figure 5, an alternate embodiment for a responsive grip is also

contemplated. Specifically, a one piece grip 310 manufactured exclusively from a viscoelastic solid-phase polymer material is disclosed. The grip 310 includes a longitudinally extending tubular shell 312 having an inner surface 318 shaped and dimensioned for attachment to the grip portion 14 of a writing implement 16 and an outer surface 322 shaped and dimensioned for gripping by an individual. The shell 312 is preferably manufactured from a silicone, thermoset elastomer containing, for example, SILASTIC, manufactured by Corning STI, although other materials may be used without departing from the spirit of the present invention. As with the shell discussed above with reference to Figures 1-4, the tubular shell shown 310 in Figure 5 is shaped and dimensioned for use as a gripping surface on a writing implement 16.

It should be appreciated that the elastomer containing, for example, KRATON or liquid silicones (such as, SILASTIC), may be altered via chemical and manufacturing processes. This alteration would likely include the softening of the thermoplastic elastomer. Also other treatments may be used without departing from the spirit of the present invention. The elastomer may also be modified to enhance its performance characteristics. For example, ultra-violet protection and/or fillers, such as Kevlar (an aramid fiber manufactured by DuPont), may be added to enhance the performance of the elastomer.

The provision of a responsive viscoelastic polymer finger surface in all three embodiments, provides users with soft and individually conforming grips. In this way, the grips are designed to enhance the tactile feel of the instrument. This improves the user's

ability to work. The soft viscoelastic surface also reduces finger and hand fatigue. The structure of the present invention is also easy to manufacture, either through the use of extrusion or injection molding. It is further contemplated that other manufacturing steps may be involved when the viscous liquid grip is utilized.

5 The practicality and durability of the present grips are also noteworthy. The inner shell on the grip provides a rigid and long-lasting shape or housing. The shell's strength is maintained even with extended use. The soft outer surface is protected and partially encased by this shell. Unlike foam and other materials, liquids will not adversely affect the grip. Its improved performance is observed with regard to finger oil absorption. The two part design prevents excessive absorption. This greatly reduces the degradation and swelling of the grip with use. The two part grip holds precise its exacting dimensions. The firm and precisely designed shell also makes installation of the grip easier. It will not catch and wrinkle as it is assembled like a soft one-piece rubber grip would.

10 The present grips also provide greater shock absorption and vibration dampening. Clearly, with regard to various sports implements and other handles, this feature is desirable and helpful to the user. The grips described above provide much more shock absorption than other grips on the market.

15 The ergonomic emphasis of this design is positive. Its use may help lower the rate of finger/hand injuries caused by excessive pressure and rigid surfaces.

20 As previously mentioned the invention relates generally to conformable grips useful in

hand gripped items. With this in mind, an alternate embodiment of the present grip for use in conjunction with a golf grip is disclosed in Figures 6 to 8. The golf grip 210, 310 is designed with a responsive and relatively viscoelastic hand surface 212, 312. The viscoelastic hand surface 212, 312 provides golfers with a soft and individually conforming hand surface. For example, the viscoelastic hand surface 212, 312 may be a responsive and relatively viscoelastic solid-phase polymer material (Figures 6 and 7) or a gelatinous material interposed within a more resilient material to contain the gelatinous material (Figure 8).

The hand surface of the present grip is an ultra-soft material. This also endows the product with an inherent tactile feel. The grip, as described herein, provides a tacky surface, essential and beneficial for gripping. The ultra-soft hand surface can be measured in terms of hardness by the Shore A Durometer Test. The present grips have durometers in this scale between approximately 2 and 40.

In accordance with a preferred embodiment of the present golf grip 210, and with reference to Figures 6 and 7, the golf grip 210 includes a shell 214 shaped and dimensioned to fit about the proximal end 216 of a golf club shaft 218. As such, the shell 214 includes an inner surface 232 shaped and dimensioned to fit about the golf club shaft. The outer surface 234 of the shell 214 is shaped and dimensioned to receive the viscoelastic hand surface 212 in a manner that will be discussed in greater detail below.

As with most golf grips, the present golf grip 210, and the shell 214, are tapered as they extend from the closed proximal end 236 to the open distal end 238. This allows the shell 214

to conform to the shape of conventional golf club shafts 218.

The shell 214 may be constructed from a variety of soft elastomers, such as, rubber or synthetic rubber-like materials. However, other materials may be employed without departing from the spirit of the present invention.

5 The shell 214 includes a central section 220 about which the viscoelastic hand surface 212 is positioned. The proximal end 222 and distal end 224 of the shell 214 are respectively provided with lips 226, 228 circumferentially extending about the shell 214. The lips 226, 228 are shaped and dimensioned to retain the viscoelastic hand surface 212 about the central section 220 of the shell 214.

10 In accordance with the embodiment disclosed in Figures 6 and 7, the viscoelastic hand surface 212 is preferably a viscoelastic solid-phase polymer material. The viscoelastic solid-phase polymer material is preferably a styrenic thermoplastic elastomer containing, for example, KRATON, which is manufactured by Shell Chemical Company.

15 The viscoelastic hand surface 212 is positioned about the shell 214, and between the proximal and distal lips 226, 228. The viscoelastic hand surface 212 is preferably adhered to the central section 220 of the shell 214 with an adhesive. It is also contemplated that the hand surface 212 may be adhered to the central section 220 of the shell 214 by over molding. With related materials over molding would create a chemical bond, in essence forging one piece containing assimilated parts. As those of ordinary skill in the art will certainly appreciate,
20 other methods for securing the hand surface 212 to the shell 214 may be employed without

departing from the spirit of present invention. Where the viscoelastic hand surface 212 is formed from a responsive, and relatively viscoelastic solid-phase polymer material, the outer surface 230 of the viscoelastic hand surface 212 is formed from the same viscoelastic material as the remainder of the hand surface 212.

5 An alternate embodiment of the present invention is disclosed in Figure 8. The alternate embodiment is substantially similar to the embodiment described above with reference to Figures 6 and 7, but replaces the viscoelastic solid-phase polymer construction with a viscous liquid material contained in an elastomeric bag.

Specifically, the golf grip 310 includes a shell 314 shaped and dimensioned to fit about the proximal end of a golf club shaft. As with the prior embodiment, the shell 314 includes a central section 320 about which the soft viscoelastic hand surface 312 is positioned. The proximal and distal ends 322, 324 of the shell 314 are respectively provided with lips 326, 328. The lips 326, 328 are shaped and dimensioned to retain the soft polymer material forming the hand surface 312 about the central section 320 of the shell 314.

15 In accordance with the embodiment disclosed in Figure 8, the viscoelastic hand surface 312 is a viscous liquid material 336 contained in an elastomeric bag 338. The viscous liquid 336 is preferably a silicone gel or oil and the elastomeric bag 338 is preferably a silicone sheet or a thermoplastic elastomer. While preferred materials are disclosed above, other materials exhibiting similar properties may be used without departing from the spirit of the present
20 invention.

The viscoelastic hand surface 312 is preferably adhered to the central section 320 of the shell 314 with an adhesive. The attachment could also be accomplished by compressing both ends of the elastomeric bag 338 at the proximal and distal lips 326, 328 with a chamber and gasket system. As those of ordinary skill in the art will certainly appreciate, other methods for securing the viscoelastic hand surface 312 to the shell 314 may be employed without departing from the spirit of present invention.

The present golf grip 210, 310 is designed such that it may be placed about the proximal end of the golf club shaft in much the same manner that conventional golf grips are placed about the proximal end of a golf club shaft. As such, the present golf grip 210, 310 may be used as a replacement grip for worn grips or grips placed upon a golf club during the manufacture of the golf club.

In accordance with the preferred embodiments of the present invention, the soft polymer material forming the hand surface 212, 312 is approximately 1/16" - 1/4" thick and the elastomeric shell 214, 314 may be less than 1/8" thick, but up to 1/4" thick. In this way, the present grip 210, 310 has substantially the same dimensions as conventional golf grips.

With reference to Figures 9 through 11, alternate embodiments for a responsive grip are also contemplated. Specifically, Figure 9 discloses a one piece grip 410 manufactured exclusively from a viscoelastic solid-phase polymer material. The grip 410 includes a longitudinally extending tubular shell 412 having an inner surface 414 shaped and dimensioned for attachment to a golf club shaft and an outer surface 416 shaped and

dimensioned for gripping by an individual. The shell 412 is preferably manufactured from a styrenic thermoplastic elastomer containing, for example, KRATON, manufactured by Shell Chemical Company, although other materials may be used without departing from the spirit of the present invention.

5 As with the shell discussed above with reference to Figures 6 to 8, the tubular shell 412 shown in Figure 9 is shaped and dimensioned for use as a golf club grip. With this in mind, the grip is slightly tapered from its closed first end 418 to its open second end 420.

10 The embodiment disclosed in Figures 10 and 11 is a wrap 510 for application to grips. The wrap is a longitudinally extending strip 512 of a viscoelastic solid-phase polymer material having a first end 514 and a second end 516, wherein the first end 514 is cut at an oblique angle to facilitate attachment of the strip 512 to the handle 518 of a sports, or other, implement. The strip 512 is of a length sufficient to be wrapped about the handle 518 and to act as a grip for the implement. The wrap 510 is preferably manufactured from a thermoplastic elastomer, for example, KRATON, manufactured by Shell Chemical, although other materials may be
15 used without departing from the spirit of the present invention. The wrap is, again, composed of the ultra-soft material, which provides unprecedented benefits and advantages to the user.

20 As shown in Figure -, the wrap 510 is secured to the handle 518 of a sports implement, or other implement, by simply encircling the handle in a conventional manner. Additionally, all-purpose adhesive tape or glue may be placed between the handle 518 and the wrap 510 to ensure the secure attachment of the wrap 510 to the handle 518.

It should be appreciated that the styrenic thermoplastic elastomer containing, for example, KRATON, may be altered via chemical and manufacturing processes. This alteration would likely include the softening of the thermoplastic elastomer. Also other treatments may be used without departing from the spirit of the present invention.

5 The provision of a responsive viscoelastic polymer hand surface provides golfers with a soft and individually conforming hand surface. In this way, the present grips are designed to enhance the feel of the golf club, and, thereby, improve the golfer's ability to strike a golf ball. A soft grip surface prompts the golfer to use a softer touch in putting and it helps to avoid excessive squeezing on other clubs. The soft viscoelastic hand surface also reduces hand fatigue associated with gripping a hard hand surface. In addition, the use of an elastomeric shell with a responsive viscoelastic polymer material encased therein makes the present golf grip easy to manufacture and place upon the proximal end of a golf club shaft for use by a golfer.

10 The present grips also provide greater shock absorption and vibration dampening. Clearly, with regard to various sports implements and other handles, this feature is desirable and helpful to the user. The grips described above provide much more shock absorption than other grips on the market.

15 While the preferred embodiments have been shown and described, it will be understood that there is no intent to limit the invention by such disclosure, but rather, is intended to cover all modifications and alternate constructions falling within the spirit and

20

scope of the invention.

CLAIMS

1. A writing implement, comprising:
a main body having a gripping portion upon which a grip is mounted;
the grip including a longitudinally extending tubular shell having an inner surface
5 abutting with the main body and an outer surface, and a viscoelastic hand/finger surface
formed about the outer surface of the tubular shell.
2. A writing implement according to claim 1, wherein the grip readily removable from
the main body of the writing implement.
- 10 3. A writing implement according to claim 2, wherein the viscoelastic hand/finger surface
is a viscoelastic solid-phase polymer material.
4. A writing implement according to claim 3, wherein the viscoelastic solid-phase
15 polymer material is a thermoplastic elastomer.
5. A writing implement according to claim 2, wherein the viscoelastic hand/finger surface
is a viscous liquid material contained within an elastomeric bag.

6. A writing implement according to claim 5, wherein the viscoelastic liquid material is a silicone gel or silicone oil.

7. A writing implement according to claim 1, wherein the grip is integrally formed with
5 the main body of the writing implement.

8. A writing implement according to claim 7, wherein the viscoelastic hand/finger surface is a viscoelastic solid-phase polymer material.

9. A writing implement according to claim 8, wherein the viscoelastic solid-phase
10 polymer material is a thermoplastic elastomer.

10. A writing implement according to claim 7, wherein the viscoelastic hand/finger surface is a viscous liquid material contained within an elastomeric bag.

11. A writing implement according to claim 10, wherein the viscoelastic liquid material is a silicone gel or silicone oil.

12. A grip adapted for attachment to an implement including a handle, comprising:
a longitudinally extending tubular shell including an inner surface shaped and
dimensioned for attachment to the handle of the implement and an outer surface; and
a viscoelastic hand surface having a thickness secured about the outer surface of the
tubular shell, wherein the tubular shell includes a first end and a second end, and the tubular
shell includes an outwardly extending first lip adjacent the first end of the tubular shell and a
outwardly extending second lip adjacent the second end of the tubular shell, the first and
second lips defining a central section within which the viscoelastic hand surface is positioned,
wherein the central section has a depth as defined by the first and second lips which is
substantially the same as the thickness of the viscoelastic hand surface such that the first and
second lips acting to retain the viscoelastic hand surface in position on the tubular shell.

13. A grip according to claim 12, wherein the first lip extends about the circumference of
the tubular shell adjacent the first end of the tubular shell and the second lip extends about the
circumference of the tubular shell adjacent the second end of the tubular shell.

14. A grip according to claim 12, wherein the viscoelastic hand surface is a viscoelastic
solid-phase polymer material.

15. A grip according to claim 14, wherein the viscoelastic solid-phase polymer material is a thermoplastic elastomer.

16. A grip according to claim 12, wherein the viscoelastic hand surface is a viscous liquid material contained within an elastomeric bag.

17. A grip according to claim 16, wherein the viscoelastic liquid material is a silicone gel or silicone oil.



18. A grip according to claim 12, wherein the tubular shell is a soft elastomer.

19. A grip according to claim 12, wherein the grip is shaped and dimensioned for use as a golf club grip.

20. A grip according to claim 19, wherein the tubular shell is substantially cylindrical shaped with a slight taper.

ABSTRACT OF THE DISCLOSURE

A grip adapted for attachment to a writing implement is disclosed. The grip includes a longitudinally extending tubular shell having an inner surface and an outer surface. The grip further includes a viscoelastic hand/finger surface formed about the outer surface of the tubular shell.






FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7





FIG. 8.






FIG. 10




FIG. 11

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

DECLARATION FOR PATENT APPLICATION

INVENTOR(S): Benjamin J. Kwitek

TITLE : VISCOELASTIC GRIP FOR A WRITING
INSTRUMENT

DOCKET NO. : KWI-003

TO THE HONORABLE COMMISSIONER OF PATENTS AND TRADEMARKS:

As a below named inventor, I hereby declare that:

This declaration is of the following type: (check one applicable item below)

☒ original
☐ design
☐ supplemental

NOTE: *If the declaration is for an International Application being filed as a divisional, continuation or continuation-in-part application do not check next item; check appropriate one of last three items.*

☐ national stage of PCT

NOTE: *If one of the following 3 items apply then complete and also attach ADDED PAGES FOR DIVISIONAL, CONTINUATION OR CIP.*

☐ divisional
☐ continuation
☒ continuation-in-part (CIP)

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor

(if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled VISCOELASTIC GRIP FOR A WRITING INSTRUMENT, the specification of which is attached hereto unless the following is checked:

____ - was filed on _____ as United States Application Number or PCT International Application Number _____, and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) or 265(b) of any foreign application(s) for patent or inventor's certificate or 365(a) of any PCT international application which designates at least one country other than the United States of America, listed below and have also identified below any foreign application for patents or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Applications:

Priority Claimed:

(Number)	(Country)	(Day/Month/Year Filed)	Yes	No
----------	-----------	------------------------	-----	----

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed below.

<u>60/163, 259</u>	<u>11/03/99</u>	<u>Pending</u>
(Application No.)	(Filing Date)	(Status - patented, pending, abandoned)

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the National or PCT international filing date of this application.

<u>09/173,445</u>	<u>10/16/98</u>	<u>Pending</u>
(Application No.)	(Filing Date)	(Status - patented, pending, abandoned)

<u>60/062,215</u>	<u>10/16/97</u>	<u>Abandoned</u>
(Application No.)	(Filing Date)	(Status - patented, pending, abandoned)

As the inventor, I hereby appoint the following attorney(s) and/or agent(s) of AQUILINO, WELSH & FLAXMAN, P.C. to prosecute this application and transact all business in the U.S. Patent and Trademark Office connected therewith. Name and registration number are listed below.

NICHOLAS J. AQUILINO	24,527
JOHN L. WELSH	33,621
HOWARD N. FLAXMAN	34,595

Please send correspondence to:

Howard N. Flaxman

AQUILINO, WELSH & FLAXMAN, P.C.

2341 Jefferson Davis Hwy

Suite 112

Arlington, Virginia 22202

Direct telephone calls to:

Howard N. Flaxman

(703) 920-1122

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

5

Full name of sole or first inventor:

Benjamin J. Kwitek

Residence : Canon City, CO

Citizenship: United States of America

Post Office Address: 1061 Valley View Drive

Canon City, CO 81212

Date: 11/03/00

Signature: Benjamin J. Kwitek